

MagiX 43-46

Electro-hydraulic scissor lift with platforms, 4.3 t capacity



Application

- Check-in
- Repair and maintenance
- Wheel alignment

Description:

- Control unit with integrated pump unit, alarm signal and digital height indication
- Electronic synchronization
- Emergency lowering valve
- Sturdy scissor construction
- No mechanical connection between scissor sections
- Optimum access to vehicle
- Variable installation width

Standard colours:

- Platforms and scissor: RAL 7016 grey
- Ramps: Galvanized

Versions:

- Available with different voltages
- S = Flush platforms
- WL = With front recesses for turn tables and rear side slip plates
- C (Combi) = Platforms with integrated free-wheel lift
- Incl. guiding edges for scissor jack for all models as standard
- Base frame galvanized as standard
- 46 = 4,650 mm platforms
- Play detector with 6 movement directions

Optional extras:

- Set of expansion bolts
- Set of rubber blocks, 80 mm
- KTL coating for platforms
- LED lightning set
- Installation frame for recessed installation
- Air hydraulic scissor jack

Special colours available on request!



Scan the QR-Code for detailed product information.

Further Information on www.autopstenhoj.com

AUTOPSTENHOJ GmbH

Sandkampstraße 90
D-48432 Rheine
☎ +49 5971 8602-02
✉ info@autopstenhoj.com

AUTOPSTENHOJ GmbH

Barrit Langgade 188-190
DK-7150 Barrit
☎ +45 76 82 13 30
✉ info@autopstenhoj.com

Technical data	
Lifting capacity	4,300 kg
Lifting height	1,850 mm
Working height	2,090 mm
Lifting / lowering time	50 sec.
Pump unit	3 kW
Voltage	3x230 / 400V – 50 Hz

Scissor platforms	
Platform length	4,650 mm
Platform width	630 mm
Distance between platforms	800 – 1,020 mm
Min. height	240 mm
Depth of recess	0 mm

Free-wheel lift	
Lifting capacity	3,500 kg
Lifting height	400 mm
Min. height	0 mm
Lifting / lowering time	8 / 8 sec.
Operation	hydraulic
Length	1,420 – 2,100 mm

