

506 202

15 METERS MAXIMUM HOSE CAPACITY

**Aluminium base and arms with composite spool hose reels, can handle up to 15 m x 1/2" hose.**



## FLUIDS HANDLED


- Air.
- Water.
- Antifreeze and Windshield Wash Solutions.
- High Pressure Hot Water.
- Synthetic and Mineral Oils.
- AdBlue® / DEF.
- Grease.

## MARKETS / APPLICATIONS

- Car and truck dealers.
- Service shops.
- Fleets.
- General manufacturing.
- Service stations.
- Lube trucks.
- Quick lubes.

## MOUNTING

- Floor.
- Wall.
- Ceiling.
- Tank.



Dimensions mm (inches)

- Aluminium base and guide arm provide the rigidity to withstand the most demanding applications while offering a reduced weight for easy installation.
- Fatigue resistant steel spring for years of durable performance and even load when pulling and recoiling the hose.
- Full port shaft and swivel for no restrictions.
- Spool mounted on two permanent lubricated and sealed ball bearings to reduce torque load on spring for smooth retraction and longer life.
- Large effective radial latching area for easier operation.
- Six roller guide outlet prevents hose pinching and reduces friction.
- Hose guide arm can be placed in different positions to accommodate any method of mounting.
- Hose reels with hose include 0,8 m inlet hose.



Reel with arms in ceiling mounting position.

PART No.	BARE REEL	HOSE IN Ø	HOSE LENGTH	CONNECTING HOSE INLET	DELIVERY HOSE OUTLET	PRESSURE RATING	WEIGHT (With hose)
<b>AIR / WATER / ANTIFREEZE SOLUTIONS</b>							
<b>506 101</b>	<b>506 910</b>	3/8"	10 m	3/8" BSP (M)	3/8" BSP (M)	15 bar	12,1 kg
<b>506 121</b>	<b>506 912</b>	3/8"	15 m	3/8" BSP (M)	3/8" BSP (M)	15 bar	14,2 kg
<b>506 122</b>	<b>506 919</b>	1/2"	15 m	1/2" BSP (M)	1/2" BSP (M)	15 bar	14,9 kg
<b>WINDSHIELD AND WINDSHIELD WASH SOLUTIONS / AdBlue® - DEF / DETERGENTS</b>							
<b>506 762</b>	<b>506 976</b>	1/2"	10 m	1/2" BSP (M)	1/2" BSP (M)	20 bar	13 kg
<b>506 782</b>	<b>506 978</b>	1/2"	15 m	1/2" BSP (M)	1/2" BSP (M)	20 bar	15,5 kg
<b>SYNTHETIC AND MINERAL OILS</b>							
<b>506 202</b>	<b>506 920</b>	1/2"	10 m	1/2" BSP (M)	1/2" BSP (M)	160 bar	12,6 kg
<b>506 222</b>	<b>506 922</b>	1/2"	15 m	1/2" BSP (M)	1/2" BSP (M)	160 bar	14,9 kg
<b>506 212*</b>	<b>506 921</b>	1/2"	15 + 3 m	1/2" BSP (M)	1/2" BSP (M)	160 bar	15,7 kg
<b>WASTE OIL SUCTION</b>							
<b>506 503</b>	<b>506 950</b>	5/8"	6 m	1/2" BSP (M)	1/2" BSP (M)	Vacuum	13,3 kg
<b>GREASE AND HYDRAULIC FLUID</b>							
<b>506 300</b>	<b>506 930</b>	1/4"	10 m	1/4" BSP (M)	1/4" BSP (M)	350 bar	12,4 kg
<b>506 301</b>	<b>506 934</b>	3/8"	10 m	3/8" BSP (M)	1/4" BSP (M)	280 bar	12,9 kg
<b>506 321</b>	<b>506 936</b>	3/8"	15 m	3/8" BSP (M)	1/4" BSP (M)	280 bar	16 kg
<b>506 311*</b>	<b>506 935</b>	3/8"	15 + 3 m	3/8" BSP (M)	1/4" BSP (M)	280 bar	17 kg
<b>HIGH PRESSURE HOT WATER (UP TO 100 °C)</b>							
<b>506 421</b>	<b>506 942</b>	3/8"	15 m	3/8" BSP (M)	1/4" BSP (M)	170 bar	15,1 kg

\*15 + 3 m models shall be need in installations allowing a minimum of 3 m of hose hanging from the reel.